

## CTL-3000 Analogue DCVG



### Features

- Accurately locate coating defects
- Estimate defect size
- Identify priority for excavation
- Monitor coating condition
- Confirm electrical continuity
- Single surveyor required
- Auto-zero function to remove bias from readings
- Comprehensive 2 year warranty

### Included

- CTL-3000
- 2 x half cell poles with cables
- 2 x Cu/CuSO<sub>4</sub> half cells
- AC charger; 120/240 V AC, 50/60 Hz input
- Carrying case
- Shoulder harness
- Operation manual

### Technical Specification

- Meter: Centre zero analogue
- Input Impedance: 10, 100, 1000 Mohm
- Measurement: Scales to 10, 20, 50, 100, 200, 500, 1000, 2000, 5000 mV
- Case: Die cast aluminum, grey baked enamel
- Dimensions: 19cm x 10cm x 13cm (7.5" x 4" x 5")
- Weight: 1.4 kg (3 lb)
- Battery: 12V 2.0 amp hour NiMH
- Half cell poles: Fiberglass, adjustable length
- Half cells: Cu/CuSO<sub>4</sub>
- Carrying Case: Plastic, IP67 rated 40.5cm x 33cm x 18cm (16" x 7" x 13")



Specifications subject to change without notice